

LOAD RADIUS (M)	Front jack extended 360 degrees Outriggers fully extended 6.1m						
	BOOM						
	10.5m BOOM	14.2m BOOM	18.0m BOOM	21.7m BOOM	25.5m BOOM	29.2m BOOM	33.0m BOOM
3.0	30.00	20.00	16.00				
3.5	25.40	20.00	16.00	12.00			
4.0	22.90	20.00	16.00	12.00	11.50		
4.5	21.00	20.00	16.00	12.00	11.50		
5.0	19.40	18.40	16.00	12.00	11.50	9.00	
5.5	17.70	16.80	14.75	12.00	11.50	9.00	7.00
6.0	16.20	15.30	13.70	12.00	11.50	9.00	7.00
7.0	13.70	12.65	11.95	11.00	10.00	9.00	7.00
8.0	11.40	11.00	10.55	10.20	8.90	8.20	7.00
9.0		9.00	9.00	9.20	8.05	7.45	6.25
10.0		7.30	7.30	7.70	7.30	6.75	5.70
12.0		5.05	5.05	5.45	5.70	5.65	4.80
14.0			3.60	4.00	4.25	4.40	4.10
16.0			2.55	2.95	3.20	3.40	3.45
18.0				2.20	2.45	2.65	2.80
20.0				1.55	1.85	2.05	2.20
22.0					1.35	1.55	1.75
24.0						1.20	1.35
26.0						0.85	1.00
28.0							0.70
30.0							0.50